



## ***ITCB FAUCET Installation***

---

### **INTRODUCTION**

This instruction details installation of the hot water faucet on the front control panel.

### **CONTENTS**

ITEM	PART NO.	QTY.	DESCRIPTION
1	12422.0009	2	Clamps
2	32591.0031	1	Tubing .5" x 14.0"
3	41193.0001	1	Tubing .375" x 1.2"
4	29075.0000	1	Faucet
5	01544.0000	1	Washer
6	29264.0000	1	Nut

### **INSTRUCTIONS**

1. With tank empty and unit unplugged – remove top cover and front panel.
2. Remove the cap and clamp from tank fitting.

**If faucet is to be installed on the front of the hood:**

**NOTE:** *It is recommended to remove the control board prior to installing the faucet to the front of the hood.*

3. Remove the black plug on the front of the bezel.
4. Install .5" ID tubing approx. 14.0" long over tank fitting and secure with 12422.009 clamp (fully tighten).
5. Insert faucet shank through the bezel and secure to hood with 01544.0000 washer and 29264.0000 nut. Make sure faucet is straight when tightening.
6. Install the short (1.2") .375" ID tubing 41193.0001 over end of faucet shank.
7. Slide loose end of the 1/2" tubing from the tank over the .375" tubing on the faucet shank. Secure with 12422.0009 clamp (fully tighten).
8. Turn on the water.
9. Plug in the brewer and allow it to fill.
10. Check the new connections for leaks.
11. Reinstall top cover and front panel.

---

### **BUNN-O-MATIC CORPORATION**

POST OFFICE BOX 3227

SPRINGFIELD, ILLINOIS 62708-3227

PHONE: (217) 529-6601 FAX: (217) 529-6644

