

Dual SH BrewWISE® Tank Temperature Adjustment

BUNN®

In certain altitudes it may be necessary to adjust the tank temperature. In areas of high altitude the tank temperature will need to lowered to prevent boiling.

This chart should be used as a guide when adjusting the brew water temperature. Brew water temperature is factory set at 200° F (93.3° C).

Altitude (Feet)	Boiling Point of Water		Recommended Water Temperature	
	°F	°C	°F	°C
-1000	213.8	101.0	200	93.3
-500	212.9	100.5	200	93.3
0	212.0	100.0	200	93.3
500	211.1	99.5	200	93.3
1000	210.2	99.0	200	93.3
1500	209.3	98.5	200	93.3
2000	208.4	98.0	200	93.3
2500	207.4	97.4	200	93.3
3000	206.5	96.9	199	92.8
3500	205.6	96.4	198	92.2
4000	204.7	95.9	197	91.7
4500	203.8	95.4	196	91.1
5000	202.9	94.9	195	90.6
5500	201.9	94.4	195	90.6
6000	201.0	93.9	194	90.0
6500	200.1	93.4	193	89.4
7000	199.2	92.9	192	88.9
7500	198.3	92.4	191	88.3
8000	197.4	91.9	190	87.8
8500	196.5	91.4	189	87.2
9000	195.5	90.8	188	86.7
9500	194.6	90.3	187	86.1
10000	193.7	89.8	186	85.6

Step 1: From the table, select the temperature based on the closest altitude to the location.

Step 2: Enter level 2 programming by pressing the right hidden switch for 5 seconds.

Step 3: Using the right hidden switch scroll to the Set Temp screen.

SET TEMP 200°

(-) **DONE** (+)

Step 4: Using the Digital (-) or Control (+) buttons adjust the temperature on the brewer's screen then select Done.

Step 5: Adjust the Set Ready temperature accordingly then select Done.

SET READY 195°

(-) **DONE** (+)

Step 6: Exit the programming menus.